


↑ place along fold of fabric & pin ↑

homemadeonourhomestead.com

Bucket Bag Sewing Pattern:

Cut (1) from exterior fabric
Cut (1) from interior fabric

Cut (1) from fusible fleece
OR
fusible foam
OR
stabilizer of your choice



Make sure you have your printer set to print at 100% and not to scale.

You may use this pattern for personal use. The items made from this pattern may be sold. The pattern itself may NOT be sold unless you have permission from homemadeonourhomestead.com.



Cutting Instructions for Bucket Bag:

(from pattern piece provided)

Cut (1) bucket bag bottom from EXTERIOR fabric

Cut (1) bucket bag bottom from INTERIOR fabric

Cut (1) piece of fusible foam or fusible fleece.

then

Cut (2) rectangles of EXTERIOR fabric 14.5" wide x 12" tall

Cut (2) rectangles of INTERIOR fabric 14.5" wide x 12" tall

Cut (2) pieces of fusible foam (preferred) or fusible fleece 14.5"
wide x 12" tall

Cut (2) pieces of webbing material 1.5" wide by 18" long
*this is for your handles so you can really make these any
length you want*

OPTIONS FOR FINISHING:

If you want to just bind the top and leave the bucket bag open, you'll also need to cut a strip of fabric 3" wide x 30" long.

This will be the binding along the top edge of your bag. You can cut this from the exterior fabric if you want it to match the exterior, you can use the interior fabric if you want it to contrast from the exterior OR you can use a completely different fabric. It's up to you and the look you want to achieve.



If you'd prefer to add a drawstring closure top for this bucket bag, you'll also need:

Cut (2) pieces from the fabric of your choice 9" tall x 14.5" wide.

SUPPLIES LIST:

*Exterior fabric (100% quilting cotton)

*Interior fabric (100% quilting cotton)

*Binding

*fusible foam OR fusible fleece.

NOTE: *fusible foam will provide more stability and therefore your bag will be able to stand up on its own when empty. Both Fusible foam and fusible fleece are washable.

Webbing for handles.

NOTE: (Material and length are up to you. Measurements provided are based on what I used).

